



code	inside diameter		outside diameter		working pressure		burst pressure		weight nominal		length max	
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	m	ft
1335626	13	1/2	22	0,87	17,5	263	70	1050	0,29	0,20	120	400
1335618	25	1	36	1,42	17,5	263	70	1050	0,65	0,43	120	400
1356852	38	1-1/2	51	2,01	17,5	263	70	1050	1,03	0,69	120	400
1335600	51	2	65,5	2,58	17,5	263	70	1050	1,51	1,01	120	400



EN

Compressed air hose and water hose for mines

Standards: AS 2660 class B.

Application: fire resistant and conductive softwall hose for compressed air and water, used in mines.

Temperature: from -15°C (+5°F) to +70°C (+158°F).

Construction

Tube: black, smooth, conductive NBR rubber, oil resistant.

Reinforcement: high strength synthetic cord.

Cover: black, smooth, (wrapped finish) in conductive CR rubber, fire, oil, and weathering resistant.

Branding: continuous orange stripe "IVG / AS 2660 B W.P. 17,5 Bar AIR/WATER FRAS".

CN

矿用导电橡胶空气及水管

质量标准: AS 2660 class B

应用范围: 该压缩空气及水管具有防火及传导性, 可用在矿山开采及要求防火的工矿

温度范围: -15° C(+5° F) 到 +70° C(+158° F)

软管结构

内层: 黑色, 光滑, 导电性NBR 橡胶, 耐油污

加强层: 高强度合成绳

外层: 黑色, 光滑(表面布纹), 导电性CR 橡胶, 防火, 耐油污, 耐侵蚀

商标: 连续橙色条状标记 "IVG / AS 2660 B W.P. 17,5 Bar AIR/WATER FRAS"

SAFETY INFORMATION – USER RESPONSIBILITIES

The service life of rubber hoses mainly depends on the dedicated use. Equipment and systems where the hose is installed must be designed safely. Since our hose can be designed for different applications, IVG Colbachini SpA cannot guarantee the proper functioning of the product for all situations. The analysis of the technical aspects related to specific uses must be performed by the users when choosing the product that meets their requirements. So, in relation to the variety of operating conditions and applications of the IVG hose, the user is solely responsible for the final choice of the product deemed suitable to satisfy the performance and safety requirements called for the application.

The information and technical data shown in the product data sheets must be examined by users with appropriate technical skills.

IVG Colbachini is not responsible for other uses, identified by the end user, that are different from the one shown in its catalogues, product sheets, offers, order confirmations and any recommendations attached.

An inappropriate choice of the product or a failure to follow the procedures of installation, use, maintenance and storage of the hoses may lead to a hose break and cause material damage and/or serious injury to people.

For the selection and proper use of the IVG products you can also refer to the document "Recommendations for selection, storage, use and maintenance of rubber hoses" provided by Assogomma and available on www.ivgspa.it.

These recommendations are according to the international standard ISO 8331, "Plastic and rubber hoses and hose assemblies - Guidelines for selection, storage, use and maintenance."

For safety reasons, never exceed the working pressure indicated in the product data sheet.

For specific applications of rubber hoses, please refer to the legal requirements or specific standards; moreover additional recommendations for particularly critical applications are available.

For further information, contact the Marketing department (marketing@ivgspa.it).