




code	inside diameter		outside diameter		working pressure		burst pressure		weight nominal		length max	
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	m	ft
1312103	16	5/8	23	0,91	10	150	30	450	0,26	0,17	120	400
1103601	20	25/32	28	1,10	10	150	30	450	0,35	0,24	120	400
1245201	25	1	33	1,30	10	150	30	450	0,43	0,29	120	400
1252941	30	1-3/16	38	1,50	10	150	30	450	0,50	0,34	120	400
1252950	35	1-3/8	44	1,73	10	150	30	450	0,67	0,45	120	400
1252968	40	1-37/64	49	1,93	10	150	30	450	0,73	0,49	120	400
1252984	45	1-49/64	54	2,13	10	150	30	450	0,82	0,55	120	400
1252992	51	2	61	2,40	10	150	30	450	1,02	0,68	120	400
1253000	60	2-3/8	70	2,76	10	150	30	450	1,18	0,79	120	400



EN

Hot water discharge hose

Application: softwall hot water discharge hose.

Temperature: from -25°C (-13°F) to +120°C (+248°F).

Construction

Tube: white, smooth, EPDM rubber.

Reinforcement: high strength synthetic cord.

Cover: red, smooth (wrapped finish), in EPDM rubber, weathering resistant.

Branding: continuous green stripe "IVG HOT (Family logo)...".

Also available upon request: 1. Different diameters 2. Yellow hose cover 3. Different working pressures.

CN

热水排放管

应用范围: 适用于输送热水

温度范围: -25° C (-13° F) 到 +120° C (+248° F)

软管结构

内层: 白色, 光滑, EPDM 橡胶

加强层: 高强度合成线绳

外层: 红色, 光滑, EPDM 橡胶, 耐侵蚀

商标: 连续绿色条状标记 "IVG HOT (公司商标)..."

可选择项: 1. 不同口径 2. 黄色外层 3. 不同工作压力

SAFETY INFORMATION – USER RESPONSIBILITIES

The service life of rubber hoses mainly depends on the dedicated use. Equipment and systems where the hose is installed must be designed safely. Since our hose can be designed for different applications, IVG Colbachini SpA cannot guarantee the proper functioning of the product for all situations. The analysis of the technical aspects related to specific uses must be performed by the users when choosing the product that meets their requirements. So, in relation to the variety of operating conditions and applications of the IVG hose, the user is solely responsible for the final choice of the product deemed suitable to satisfy the performance and safety requirements called for the application.

The information and technical data shown in the product data sheets must be examined by users with appropriate technical skills.

IVG Colbachini is not responsible for other uses, identified by the end user, that are different from the one shown in its catalogues, product sheets, offers, order confirmations and any recommendations attached.

An inappropriate choice of the product or a failure to follow the procedures of installation, use, maintenance and storage of the hoses may lead to a hose break and cause material damage and/or serious injury to people.

For the selection and proper use of the IVG products you can also refer to the document "Recommendations for selection, storage, use and maintenance of rubber hoses" provided by Assogomma and available on www.ivgspa.it.

These recommendations are according to the international standard ISO 8331, "Plastic and rubber hoses and hose assemblies - Guidelines for selection, storage, use and maintenance."

For safety reasons, never exceed the working pressure indicated in the product data sheet.

For specific applications of rubber hoses, please refer to the legal requirements or specific standards; moreover additional recommendations for particularly critical applications are available.

For further information, contact the Marketing department (marketing@ivgspa.it).