




code	inside diameter		outside diameter		working pressure		burst pressure		weight nominal		length max	
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	m	ft
1055429	76	3	94	3,70	6	90	18	270	2,63	1,76	120	400
1090380	90	3-35/64	106	4,18	6	90	18	270	2,63	1,77	120	400
1056760	102	4	116	4,57	6	90	18	270	2,64	1,77	120	400
1257064	102	4	112	4,41	5	75	15	225	1,73	1,17	120	400
1456032	102	4	120,5	4,75	5	75	15	225	3,42	2,30	120	400
1457411	102	4	122	4,81	5	75	15	225	3,67	2,47	120	400
1463462	102	4	118	4,65	5	75	15	225	2,93	1,97	120	400
1292781	127	5	139	5,48	5	75	15	225	2,77	1,86	120	400


EN

Dry abrasive materials delivery hose

Application: softwall bulk materials handling hose made with antistatic and abrasion resistant rubber. Suitable to convey cement, sand, gravel, silica, and other dry abrasive materials.

Temperature: from -40°C (-40°F) to +70°C (+158°F).

Construction

Tube: black, smooth, NR/SBR rubber with good resistance in handling abrasive materials.

Reinforcement: high strength synthetic cord.

Cover: black, smooth (wrapped finish), NR/SBR rubber, abrasion resistant.

Branding: continuous red stripe "IVG Truck (family logo)...".

Also available upon request: 1. Different diameters 2. Different working pressures.

RU

Рукав для подачи сухих абразивных веществ

Применение: напорный рукав из синтетического антистатического каучука, устойчивого к истиранию для подачи цемента, песка, гравия, кремния и других сухих абразивных материалов.

Температура: от -40° до +70°С.

Конструкция

Внутренний слой: черный, гладкий из смеси синтетического и натурального каучука NR/SBR устойчивый к абразивным материалам.

Усиление: высокопрочный синтетический корд.

Покрытие: черное, гладкое (с отпечатком текстильного бандажа) из смеси синтетического и натурального каучука NR/SBR, устойчивый к истиранию.

Маркировка: красная маркировочная лента "IVG Truck (логотип сферы применения)...".

В наличии по запросу: 1. Другие диаметры 2. Другие рабочие давления.

SAFETY INFORMATION – USER RESPONSIBILITIES

The service life of rubber hoses mainly depends on the dedicated use. Equipment and systems where the hose is installed must be designed safely. Since our hose can be designed for different applications, IVG Colbachini SpA cannot guarantee the proper functioning of the product for all situations. The analysis of the technical aspects related to specific uses must be performed by the users when choosing the product that meets their requirements. So, in relation to the variety of operating conditions and applications of the IVG hose, the user is solely responsible for the final choice of the product deemed suitable to satisfy the performance and safety requirements called for the application.

The information and technical data shown in the product data sheets must be examined by users with appropriate technical skills.

IVG Colbachini is not responsible for other uses, identified by the end user, that are different from the one shown in its catalogues, product sheets, offers, order confirmations and any recommendations attached.

An inappropriate choice of the product or a failure to follow the procedures of installation, use, maintenance and storage of the hoses may lead to a hose break and cause material damage and/or serious injury to people.

For the selection and proper use of the IVG products you can also refer to the document "Recommendations for selection, storage, use and maintenance of rubber hoses" provided by Assogomma and available on www.ivgspa.it.

These recommendations are according to the international standard ISO 8331, "Plastic and rubber hoses and hose assemblies - Guidelines for selection, storage, use and maintenance."

For safety reasons, never exceed the working pressure indicated in the product data sheet.

For specific applications of rubber hoses, please refer to the legal requirements or specific standards; moreover additional recommendations for particularly critical applications are available.

For further information, contact the Marketing department (marketing@ivgspa.it).