




code	inside diameter		outside diameter		working pressure		burst pressure		weight nominal		bending radius		length max	
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	mm	inch	m	ft
1451189	6	17/72	13	0,51	10	150	30	450	0,13	0,09	50	2,0	100	328
1452703	8	5/16	15	0,59	10	150	30	450	0,16	0,11	65	2,6	100	328
1451197	10	25/64	17	0,67	10	150	30	450	0,19	0,13	80	3,2	100	328
1451200	13	1/2	20	0,79	10	150	30	450	0,23	0,16	105	4,1	60	200
1452053	15	19/32	23	0,91	10	150	30	450	0,28	0,19	120	4,7	60	200
1449834	19	3/4	27	1,06	10	150	30	450	0,37	0,25	150	5,9	60	200


EN

Extruded hose for fuels, for use at low temperatures

Application: suitable for delivery of all types of gasoline, or for lubrication and greasing in different services. Appropriate for use at low temperatures.

Temperature: from -40°C (-40°F) to +80°C (+176°F).

Construction

Tube: black, seamless, conductive, synthetic rubber, suitable to convey all types of gasoline included unleaded gasoline and oils with aromatic content up to 50%.

Reinforcement: high strength synthetic fabrics.

Cover: black, seamless, conductive, synthetic rubber, resistant to fuel, oil, and ozone.

Electrical Resistance: tube $R \leq 1 \times 10^6 \Omega/m$, cover $R \leq 1 \times 10^6 \Omega/m$

Branding: IVG RUBBER HOSE GREEN CARBUR COLD 10 BAR W.P. - SIZE - 50 % Aromatico - BATCH NUMBER.

RU

Экструдированный рукав для различных видов топлива, для использования при низких температурах

Применение: предназначен для подачи неэтилированного бензина, дизельного топлива, экодизеля, а также для смазочных масел в различных сферах применения. Пригоден для использования при низких температурах.

Температура: от -40°C до +80°C.

Конструкция

Внутренний слой: чёрный, гладкий из токопроводящего синтетического каучука, устойчивый к неэтилированному бензину и к нефтепродуктам с ароматическим содержанием до 50%.

Усиление: высокопрочное текстильное волокно.

Покрытие: чёрное, гладкое, из токопроводящего синтетического каучука, устойчивое к нефтепродуктам, атмосферным воздействиям и маслам.

Электрическое сопротивление: внутренний слой $R \leq 1 \times 10^6 \Omega/m$, покрытие $R \leq 1 \times 10^6 \Omega/m$.

Маркировка: IVG RUBBER HOSE GREEN CARBUR COLD 10 BAR W.P. - SIZE - 50 % Aromatico - BATCH NUMBER.

SAFETY INFORMATION – USER RESPONSIBILITIES

The service life of rubber hoses mainly depends on the dedicated use. Equipment and systems where the hose is installed must be designed safely. Since our hose can be designed for different applications, IVG Colbachini SpA cannot guarantee the proper functioning of the product for all situations. The analysis of the technical aspects related to specific uses must be performed by the users when choosing the product that meets their requirements. So, in relation to the variety of operating conditions and applications of the IVG hose, the user is solely responsible for the final choice of the product deemed suitable to satisfy the performance and safety requirements called for the application.

The information and technical data shown in the product data sheets must be examined by users with appropriate technical skills.

IVG Colbachini is not responsible for other uses, identified by the end user, that are different from the one shown in its catalogues, product sheets, offers, order confirmations and any recommendations attached.

An inappropriate choice of the product or a failure to follow the procedures of installation, use, maintenance and storage of the hoses may lead to a hose break and cause material damage and/or serious injury to people.

For the selection and proper use of the IVG products you can also refer to the document "Recommendations for selection, storage, use and maintenance of rubber hoses" provided by Assogomma and available on www.ivgspa.it.

These recommendations are according to the international standard ISO 8331, "Plastic and rubber hoses and hose assemblies - Guidelines for selection, storage, use and maintenance."

For safety reasons, never exceed the working pressure indicated in the product data sheet.

For specific applications of rubber hoses, please refer to the legal requirements or specific standards; moreover additional recommendations for particularly critical applications are available.

For further information, contact the Marketing department (marketing@ivgspa.it).