




code	inside diameter		outside diameter		working pressure		burst pressure		weight nominal		length max	
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	m	ft
1193201	16	5/8	26	1,02	10	150	30	450	0,41	0,28	120	400
1177834	25	1	35	1,38	10	150	30	450	0,58	0,39	120	400



EN

Hose for conditioning systems

Application: softwall hose used for delivery of water and hot water in air conditioning systems and in heating systems.

Temperature: from -40°C (-40°F) to +120°C (+248°F).

Construction

Tube: black, smooth, synthetic rubber, heat resistant.

Reinforcement: high strength synthetic cord.

Cover: black, smooth (wrapped finish), synthetic rubber, heat, weathering and ozone resistant.

Branding: stripe available in different colours in order to identify the inlet and the outlet, with arrow indicating the direction of the fluid.

Also available upon request: 1. Different diameters. 2. Hose cover in different colours.

CN

游艇空调管

应用范围: 软壁胶管，用于游艇空调系统和加热系统输送水及热水。

温度范围: -40° C (-40° F) 到 +120° C (+248° F)。

软管结构

内层: 黑色，光滑，合成橡胶，耐热。

加强层: 高强度合成线绳。

外层: 黑色，光滑（表面布纹），合成橡胶，耐热，耐臭氧，耐老化。

商标: 用不同颜色的商标带区别进口和出口，用箭头指示液流方向。

可选择项: 1. 不同口径 2. 不同颜色的外胶。

SAFETY INFORMATION – USER RESPONSIBILITIES

The service life of rubber hoses mainly depends on the dedicated use. Equipment and systems where the hose is installed must be designed safely. Since our hose can be designed for different applications, IVG Colbachini SpA cannot guarantee the proper functioning of the product for all situations. The analysis of the technical aspects related to specific uses must be performed by the users when choosing the product that meets their requirements. So, in relation to the variety of operating conditions and applications of the IVG hose, the user is solely responsible for the final choice of the product deemed suitable to satisfy the performance and safety requirements called for the application.

The information and technical data shown in the product data sheets must be examined by users with appropriate technical skills.

IVG Colbachini is not responsible for other uses, identified by the end user, that are different from the one shown in its catalogues, product sheets, offers, order confirmations and any recommendations attached.

An inappropriate choice of the product or a failure to follow the procedures of installation, use, maintenance and storage of the hoses may lead to a hose break and cause material damage and/or serious injury to people.

For the selection and proper use of the IVG products you can also refer to the document "Recommendations for selection, storage, use and maintenance of rubber hoses" provided by Assogomma and available on www.ivgspa.it.

These recommendations are according to the international standard ISO 8331, "Plastic and rubber hoses and hose assemblies - Guidelines for selection, storage, use and maintenance."

For safety reasons, never exceed the working pressure indicated in the product data sheet.

For specific applications of rubber hoses, please refer to the legal requirements or specific standards; moreover additional recommendations for particularly critical applications are available.

For further information, contact the Marketing department (marketing@ivgspa.it).